



**PGV Series** countersink plug vent is designed to fit flush with the surface while offering free exchange of filtered air vent to atmosphere. These countersink plug vents can be installed easily into single acting cylinders, gear boxes, storage tanks or other vessels and valves, whenever pressure equalization is required.

Supplied with standard male pipe thread with internal hex, unit can be easily installed with a hex key with little or no protrusion. Nickel-plated brass body and 40 micron is standard, optional 10 or 90 micron filter element is available.

## SPECIFICATIONS

ITEM	MODEL	PGV-18	PGV-28	PGV-38	PGV-48
CONNECTION	NPTM	1/8"-27	1/4"-18	3/8"-18	1/2"-14
OVERALL LENGTH	IN.	.354"	.472"	.492"	.610"
INTERNAL HEX	IN.	1/4"	5/16"	3/8"	3/8"
MATERIAL	BODY	NICKEL PLATED	NICKEL PLATED	NICKEL PLATED	NICKEL PLATED
	ELEMENT	SINTERED BRONZE 40Micron	SINTERED BRONZE 40Micron	SINTERED BRONZE 40Micron	SINTERED BRONZE 40Micron
MAX OPERATING PRESSURE		150 PSI	150 PSI	150 PSI	150 PSI
OPERATING TEMPERATURE		35°F to 300°F	35°F to 300°F	35°F to 300°F	35°F to 300°F
WEIGHT (APPROX)	OZ.	0.09	0.22	0.39	.84
UNIT PAK	EA	10	10	10	5