



SSBV-Series low profile breather vents are constructed with 300-Series stainless steel materials, they are resistant to atmospheric corrosion, foodstuffs, sterilizing solutions, many organic chemicals, dyestuffs and wide variety of inorganic chemicals.

SSBV-Series compact breather vents are furnished with standard male pipe thread connections, they are often used on single acting stainless steel cylinders or valves to prevent dirt and foreign particles from entering port open to the atmosphere. Other common uses can also be found on vacuum relief or pressure equalization for gearboxes, crank cases, storage tanks or other vessels whenever pressure equalization is required.

Unit should be mounted in a protective position free from excessive vibration. Use wrench on hex head to tighten unit to the device. All units contact 70-micron filter element.

SPECIFICATIONS

ITEM	MODEL	AV SSBV-18	AV SSBV-28	AV SSBV-38	AV SSBV-48	AV SSBV-68	AV SSBV-88
CONNECTION	NPTM	1/8"	1/4"	3/8"	1/2"	3/4"	1"
OVERALL LENGTH	IN.	19/32"	49/64"	29/32"	1-1/32"	1-11/64"	1-1/4"
HEX	IN.	1/2"	5/8"	3/4"	15/16"	1-1/8"	1-1/2"
MATERIAL	BODY	303SS	303SS	303SS	303SS	303SS	303SS
	ELEMENT	316SS 70Micron	316SS 70Micron	316SS 70Micron	316SS 70Micron	316SS 70Micron	316SS 70Micron
MAX OPERATING PRESSURE		150 PSI	150 PSI	150 PSI	150 PSI	150 PSI	150 PSI
OPERATING TEMPERATURE		35°F to 392°F	35°F to 392°F	35°F to 392°F	35°F to 392°F	35°F to 392°F	35°F to 392°F
WEIGHT (APPROX)	OZ.	0.27	0.54	0.81	1.36	2.11	3.31
UNIT PAK	EA	5	5	2	2	1	1